



PRODUCT DATA SHEET

MARINEDECK®interior
Adhesive
Primer
Decreaser
Deck



Technical information

Angle	<0,25
Weight	about 2 kg
To apply	MARINEDECK®interior can be applied on all floors for indoor use as per European standard EN 685, being applicable on elastic floors. This classification enables architects and/or end-users for the right type of floor.
Pleasure and commercial boats	All rooms on commercial and pleasure boats, hotel rooms, offices, conference rooms, passages and corridors, class rooms, shops, hospitals, libraries and museums.
Fire resistance	(A) B1 (A) Din 4102 (B) Approved (B) SIS 024825 NT Fire 07 (C) M3 (C) NF-P-92501 (R P) (D) Q1 (little smoke emission) (D) Önorm B 3800 (E) B1 (E) Önorm B 3810
Resistance against cigarettes	Contact: light carbonisation
Single marks	Extinguishing cigarettes: light carbonisation, decreased by rubbing
Effects of chairs and wheels	MARINEDECK®interior has got the right resistance to move forward office chairs on wheels or wheel chairs. (A) Chairs on wheels: no visual effects after 25000 cycli, NEN 425 (B) >0,1 mm; class 7 on the scale of 3-7, SIS 923507 (C) Suitable (no damage after 75000 rotations). DIN 54324 (D) Suitable (no damage after 100000 rotations) norm B 5214
Electrical conductivity	ASTM D 991, BS2044 part ISO 1953 or equivalent
Reduction of contact noise	MARINEDECK®interior has excellent acoustical properties and insulates indoor, outdoor and sandwich constructions 20 DB in accordance to NP 669, 15 DB in accordance to Din 52210
Ability to recover	The structure of the MARINEDECK®interior gives an excellent recovery after a short and long lasting compression.
Wear resistance	0,028 mm in accordance to DIN 51963 (EN 660-1), Class 6, (>70000 cycli) in accordance to SS923351, Frick-Taber NP EN 602-1
Stain resistance	MARINEDECK®interior is limited resistant to chemicals
Cleaning	By clean water and natural soap (no chemicals)
Heat conduction	DIN 52612
Heat delivery	DIN 52614

Available sizes

	Article code	Length	Width	Thickness
Plank/strip	INT03619004	1900 mm	36 mm	4 mm
Plank/strip	INT03640004	4000 mm	36 mm	4 mm
Plank/strip	INT03680004	8000 mm	36 mm	4 mm
Plank/strip	INT05019004	1900 mm	50 mm	4 mm
Plank/strip	INT05040004	4000 mm	50 mm	4 mm
Plank/strip	INT05080004	8000 mm	50 mm	4 mm
Plank/strip	INT07519004	1900 mm	75 mm	4 mm
Plank/strip	INT07540004	4000 mm	75 mm	4 mm
Plank/strip	INT07580004	8000 mm	75 mm	4 mm
Plank/strip	INT10019004	1900 mm	100 mm	4 mm
Plank/strip	INT10040004	4000 mm	100 mm	4 mm
Plank/strip	INT10080004	8000 mm	100 mm	4 mm
Plank/strip	INT12519004	1900 mm	125 mm	4 mm
Plank/strip	INT12540004	4000 mm	125 mm	4 mm
Plank/strip	INT12580004	8000 mm	125 mm	4 mm
Plank/strip	INT15019004	1900 mm	150 mm	4 mm
Plank/strip	INT15040004	4000 mm	150 mm	4 mm
Plank/strip	INT15080004	8000 mm	150 mm	4 mm

COMFORTABLE MARINE FLOORS
EXCELLENCE BY NATURE