



**SECUTRED**

## PRODUCT DATA SHEET

Stazo®SecuTred  
**Adhesive**  
**Primer**  
**Decreaser**  
**Deck**



Angle	>0,25 mm
Weight in kos per m2	about 2,8 kg
To apply	STAZO® SecuTred can be applied to all decks for outdoor use as per European standard EN 685, being applicable on elastic floors. This classification enables architects and/or end-users for the right type of floor.
Commercial boats/business use	All rooms on commercial and pleasure boats, hotel rooms, offices, conference rooms, passages and corridors, class rooms, shops, hospitals, libraries and museums.
Fire resistance	(A) B1 (A) Din 4102 (B) approved (B) SIS 024825 NT Fire 007 (C) M3 (C) NF-P-92501 (R P) (D) Q1 (little smoke emission (D) Önorm B 3800 (E) B1 (E) Önorm B 3810\
Resistance against cigarettes	Contact: light carbonisation.
Single marks	Extinguishing cigarettes: light carbonisation, decreased by rubbing.
Pressure effects	STAZO Secutred has been tested in accordance to the following pressure in combination with moving modules: (A) Wheeled pressure: no visual effects after 25000 cycli, EN 425 (B) >0,1mm: class 7 on the scale of 3-7, SIS 923507 (C) Suitable (no damage after 75.000 rotations) DIN 54324 (D) Suitable (no damage after 100.000 rotations) Önorm B 5214
Electrical conductivity	ASTM D 991, BS2044 part ISO 1953 or equivalent
Reduction of contact noise	STAZO® SecuTred has the following acoustical properties and insulates outdoor and sandwich constructions by: 20 DB in accordance to NP 669 15 DB in accordance to DIN 52210
Wear resistance	0,028 mm in accordance to DIN 51963 (EN 660-1), Class 6 (>70.000 cycli) in accordance to SS923351, Frick-Taber NP EN 602-1.
Stain resistance	STAZO® SecuTred is limited resistant to chemicals. Cleaning by water and natural soap (no chemicals)
Heat conduction	DIN 52612
Heat delivery	DIN 52614

**THE COMFORTABLE MARINE NON SKID**  
**EXCELLENCE BY NATURE**