



©
ADAPTERS + BORES

1 = adapter Delrin, 2 = adapter Aluminium
3 = adapter Aluminium and 4 = adapter stainless steel

A = front side shaft, B = rear side shaft, C = length of the shaft, D = width of the key,
E = height of the key above the shaft

Ordernumber ↓	Steering system ↓	A size ↓	B size ↓	C size ↓	D size ↓	E size ↓
Standard adapters						
1: 75.10410 * 2: 75.10510 * 4: 75.10710	Federal1250/1350 Hynautic Kobelt 7031 Nauticomb LS 35/ 60/85/105/150/330 Tenfjord H28/45/58 Teleflex Hydrive LS 430 Wagner 700/701	17 17,25 17,4	19 19 19,5	25 25 25,5	5 5 5	3 3 3
1: 75.10420 * 2: 75.10520 * 4: 75.10720 *	M.T. 30/50 Whitlock	18	25	25	5	3
1: 75.10450 * 2: 75.10550 * 4: 75.10750 *	Cinkel Edson Satin Siltala Wagner B1/B2 B3/B4 incl. Spacer	25,4 25,4 25 25,4 25,4	25,4 25,4 25,4 25,4 25,4	55 61 33 50 51	6,3 6,3 6,3 6,5 6,3	3,2 3,2 3,2 3 3,5
Adapters/bores with special bore in Hub						
2: 75.10511 *	Blind 25 mm lang	0	0	25	0	0
1: 75.10412 2: 75.10512	Danfoss D 100 A	22,6	25	25	6	3
1: 75.10413 2: 75.10513	Danfoss OTPB/ OSP50/75/100/	20,53	22	25	5	3
2:75.10514	Danfoss OSPB OSPC/125/200/315	23,2	24,6	25	5	3
1: 75.10416 2: 75.10516	Goyot	17,5	19,5	25	6	4
1: 75.10417 2: 75.10517	Handpomp NS 28 incl.spacer	18	18	35	5	3
3:75.10618	Handpomp NS 50/75/ 160	34	34	70	10	4
2:75.10570	Hydrive groot LS 431/432/531/532	19,7	22	26	6	3
3:75.10619	Hydrive LS 433	28	28	45	8	3,5
1:75.10433 2:75.10533	M.T.P. 42 Vetus	17,6	19,6	31	5	3
1: 75.10432 2: 75.10532	Nauticat with special ring	17,2	19	21,7	5	3
1: 75.10444 2: 75.10544	Nauti style incl.spacer	25	25	25	6,3	4
1: 75.10421 2: 75.10521	Orbitrol klein	21,2	22,5	25	5	3

STAZO steering wheels of fortune

www.stazo.nl



ADAPTERS + BORES

1 = adapter Delrin, 2 = adapter Aluminium
3 = adapter Aluminium and 4 = adapter stainless steel

A = front side shaft, B = rear side shaft, C = length of the shaft, D = width of the key,
E = height of the key above the shaft



Page 2 adapters/bores with special hubs

1: 75.10422	Servi E 185 F	18	18	40	6	3
2: 75.10522	Incl. spacer					
1: 75.10423	Servi E 187 F/225F/	25	25	40	8	3,5
2: 75.10523	227F. incl. spacer					
1: 75.10424	Servi E 285/E 287	25	25	45	8	3,5
2: 75.10524	incl. spacer					
3:75.10625	Servi E405F/407F	30	30	58	10	4
1: 75.10426	Tenfjord H30S	17	22	25	5	3
2: 75.10526						
1: 75.10427	Tenfjord H 50	22	22	36	5	3
2: 75.10527	Incl. spacer					
1: 75.10428	Tenfjord H 68	22	22	36	5	3
2:75.10528	incl. Spacer					
3:75.10629	Tenfjord H165/	30	30	53	8	4
	H330					
1: 75.10460 *	Prebored	10	10	25	0	0
2: 75.10560 *						
3:75.10631	Willes Ridley	31,75	31,75	51	8	4
1: 75.10430	STAZO konus 1	16	20	40	4	2
2: 75.10530						
1: 75.10440	STAZO konus 2	19	25	60	4	2
2: 75.10540						
3:75.10634	STAZO konus 3	23	30	70	6	2
3:75.10635	STAZO konus 4	27	35	80	8	2,5
1: 75.10471	Adapter/ bore in accordance to your drawing					
2: 75.10571	smaller than 26 mm.					
3. 75.10671						
3:75.10641	Bore smaller than 40 mm, in accordance to specification					

